

512,143

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
6 November 2003 (06.11.2003)

PCT

(10) International Publication Number
WO 03/090996 A1

- (51) International Patent Classification⁷: **B29C 47/06**
- (21) International Application Number: PCT/US03/10237
- (22) International Filing Date: 4 April 2003 (04.04.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10/132,517 26 April 2002 (26.04.2002) US
- (71) Applicant (for all designated States except US): **CLOEREN INCORPORATED** [US/US]; 401 16th Street, Orange, TX 77630 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **CLOEREN, Peter, F.** [US/US]; 6325 Bent Water Drive, Orange, TX 77632 (US).
- (74) Agent: **KROBOTH, Timothy, R.**; Kroboth Law Office, 5501 Providence Country Club Drive, Charlotte, NC 28277-2636 (US).

(81) Designated States (national): CN, CZ, JP, US.

(84) Designated States (regional): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).

Declarations under Rule 4.17:

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations CN, CZ, JP, European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR)
- as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii)) for the following designations CN, CZ, JP, European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR)
- of inventorship (Rule 4.17(iv)) for US only


Published:

- with international search report

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR ORIENTING LAYERS IN MULTILAYERED COMPOSITES

(57) **Abstract:** A method for forming a layered composite (62) uses extrusion apparatus including a coextrusion structure (226) and a partition member (228). The relative orientation of first and second flow streams are reoriented within the extrusion apparatus and melt laminated to form the layered composite (62). The reorientation occurs via a flow sequencer (250). The coextrusion structure (226) may also include one or more removably disposed, flow-shaping inserts (206, 207, 208, 209), and the partition member (228) may be a removably disposed partition plate.



WO 03/090996 A1